



Designed for dedicated home cinemas with an acoustically transparent screen

Minimum screen size 16:9 HDTV 92" (2037 x 1146mm)
Minimum screen size 21:9 scope 90" (2101 x 900mm)

MX-5 LCR	
Frequency Range	40 Hz - 20 kHz
Power Handling	100 - 300 Watts RMS recommended amplifier power
Sensitivity	92 dB (2.83V / 1m)
Impedance	8 Ohms
Configuration	2-Way
Low Frequency Driver	Single 205mm (8") paper cone driver. 38mm (1½") voice coil wound on high powered aluminium former, with ventilated magnet assembly and copper shorting ring for low distortion
High Frequency Driver	26mm (1") doped fabric dome with large roll surround. Ferro fluid cooled. Coupled to a Krix designed 90 x 40 short throw waveguide

MX-5 Subwoofer	
Frequency Range	30 Hz - 200 Hz
Power Handling	200 - 350* Watts RMS recommended amplifier power *The use of a power amplifier with high pass filter and soft limiter function is strongly recommended on MX subwoofers.
Sensitivity	90 dB (2.83V / 1m)
Impedance	4 Ohms
Configuration	Bass reflex, down firing vent
Low Frequency Driver	Nominal 275mm (11") diameter doped paper cone driver, 50mm (2") voice coil wound on high powered Kapton former, with vented magnet assembly