

VOLCANIX SUBWOOFER

The Volcanix is the peak of home theatre bass delivery. Effortlessly reproducing the sheer energy of a high-powered explosion on your screen, the impact of a kick drum, or the subtleties of a double bass, all at the tip of your fingers.

With push-button controls conveniently located behind the grille, there's no need to pull this subwoofer out from the wall to make adjustments – it's all right there in front of you.

A massively powerful 305mm long-throw bass driver is at the heart of the Volcanix, developed specifically for highlevel, low frequency reinforcement. Krix's own amplifier design using ICEpower® class D technology is also built in, increasing efficiency and lowering power consumption.

Simple controls allow for easy set-up, with a back-lit LCD display that fades in brightness after 45 seconds, this extreme bass experience not only sounds great, it looks great too with your choice of classic black woodgrain or five genuine timber veneer finishes.

For the ultimate sound experience at home, play it through Krix.





FEATURES

- Ultimate bass power and extension
- Exclusive Krix digital sub amplifier (KDSA)
- Precise low frequency reproduction

	Volcanix
Frequency Range	15 Hz - 200 Hz (in room response)
Amplified Power	450 Watts RMS
Output	125 dB maximum SPL in room response
Inputs	Stereo line level RCA. High level inputs
Enclosure Type	Bass reflex, front vented
Low Frequency Driver	Nominal 305mm (12") diameter paper cone driver with 50mm (2") long throw voice coil developed for high level, low frequency reinforcement
Power On/Off	Adjustable Auto/Always On
Phase Select	0° to 180° continuously variable (relative to input signal)
Low Pass Filter	50 Hz-195 Hz or bypass
Dimensions	506mm high x 400mm wide x 470mm deep
Net Weight	23 kg

krix.com

FINISHES









Walnut

Black Woodgrain

Black Ash

Atlantic Jarrah

Blackwood



krix.com

ADELAIDE | 14 Chapman Road, Hackham, SA, 5163, Australia T+61 8 8384 3433 F+61 8 8384 3419 listen@krix.com.au

Pg. 2 of 2

Volcanix Specifications Sheet-002